

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF600/ 60R28 NRO	DW21B DW20B	597 23.5	1431 56.3	623 24.5	4226 166.4	157D	0.8	5540	2580	2410	2410	2190	1.6	3370	
							12	12200	5680	5310	5310	4820	23	7420	
							1.2	7040	3280	3060	3060	2780	2	4280	
							17	15510	7220	6740	6740	6120	29	9430	
							1.4	7710	3590	3350	3350	3050	2.2	4690	
							20	16980	7910	7380	7380	6720	32	10330	
							1.6	8330	3880	3620	3620	3290	2.4	5070	
							23	18350	8550	7970	7970	7250	35	11170	
							2	9490	4420	4130	4125	3750	2.8	5780	
29	20900	9740	9100	9090	8260	41	12730								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards