

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)											
				SW	OD				Speed, km/h (mph)											
				mm/in	mm/in				mm/in	mm/in	Static	10	20	30	40	50				
520/ 85R42	157A8/B	TL	DW16L DW18L	530 20.87	1951 76.81	889 35.00	5792 228.0	bar	6330	4130	3380	2940	2750	2750						
								psi												
								0.8												
								12							13940	9100	7440	6480	6060	6060
								1							7200	4700	3850	3350	3130	3130
								15							15860	10350	8480	7380	6890	6890
								1.3							8400	5480	4490	3910	3650	3650
								19							18500	12070	9890	8610	8040	8040
1.6	9490	6190	5070	4410	4125	4130														
23	20900	13630	11170	9710	9090	9100														

All tires confirms ETRTO T&RA & STRO standards