

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)							
		SW	OD	Radius	mm	Speed			Constant load					Cyclic operation		
		mm	mm	mm	mm	bar			10	20	30	40	50	10	15	
		in	in	in	in	psi			6	12	19	25	31	6	9	
300/ 75R18	W9	295	908	409	2710	142 A8/B	1.6	3130	1700	1480	1410	1360	1360	2040	1820	
							23	6890	3740	3260	3110	3000	3000	4490	4010	
	W10						3.0	4530	2460	2150	2050	1970	1970	2960	2640	
							44	9980	5420	4740	4520	4340	4340	6520	5810	
	4.0						5360	2910	2540	2420	2330	2330	3500	3120		
	58						11810	6410	5590	5330	5130	5130	7710	6870		
	5						6100	3310	2890	2760	2650	2650	3980	3550		
	73						13440	7290	6370	6080	5840	5840	8770	7820		