

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)							
		SW	OD	Radius	mm	Speed			Constant load					Cyclic operation		
		mm	mm	mm	mm	bar			10	20	30	40	50	10	15	
		in	in	in	in	psi			6	12	19	25	31	6	9	
480/ 80R26	W15L	479	1428	636	4262	167 A8/B	1.6	7340	3990	3480	3320	3190	3190	4790	4270	
							23	16170	8790	7670	7310	7030	7030	10550	9410	
	W16L	18.9	56.2	25.0	168		2.2	8830	4800	4190	3990	3840	3840	5760	5150	
							32	19450	10570	9230	8790	8460	8460	12690	11340	
	W18L						3.2	10990	5980	5210	4970	4780	4780	7170	6410	
							46	24210	13170	11480	10950	10530	10530	15790	14120	
								4	12540	6810	5940	5670	5450	5450	8180	7300
								58	27620	15000	13080	12490	12000	12000	18020	16080