

YIELDMAX



FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability

FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning


FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance

MACHINERY



Harvester

Size	Rim	Type	Unloaded dimension		Static Loaded		Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)					Cyclic operation CHO	
			SW	OD	Radius					Speed, km/h (mph)					10	15
			mm	mm	mm	mm	Constant load					6	9			
			in	in	in	in	Speed Symbol	bar	Static	10	20			30	40	50
900/60R32 CHO SB*	DW28B, DW27B, DW30B	TL	896	1893	871	5697	193A8/B	0.8	9060	5910	4850	4220	3940	3940	7090	6500
			35.3	74.5	34.3	224.3		12	19960	13020	10680	9300	8680	8680	15620	14320
								1.6	13590	8870	7270	6320	5910	5910	10640	9750
								23	29930	19540	16010	13920	13020	13020	23440	21480
								2	15480	10100	8280	7200	6730	6730	12110	11100
								29	34100	22250	18240	15860	14820	14820	26670	24450
								3	19620	12800	10490	9130	8530	8530	15350	14070
								44	43220	28190	23110	20110	18790	18790	33810	30990
								4	23210	15140	12410	10800	10090	10090	18160	16650
								58	51120	33350	27330	23790	22220	22220	40000	36670
								4.5	24860	16220	13300	11570	10810	10810	19460	17840
								65	54760	35730	29300	25480	23810	23810	42860	39300
								5	26450	17250	14150	12310	11500	11500	20700	18980
				73	58260	38000	31170	27110	25330	25330	45590	41810				

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards