

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Load Index Speed Symbol	Infl. Press.	Maximum load, kg (lbs) Speed, km/h (mph)						
			SW	OD					MIXED APPLICATION				CYCLIC*		
			mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	bar	psi	
VF 750/ 75R46	DW25B	TL	750 29.5	2294 90.3	1001 39.4	6774 266.7	189D	0.8	13870	6630	6270	6030	5490	1.6	8440
								12	30550	14600	13810	13280	12090	23	18590
								1.2	17570	8400	7950	7640	6950	2	10700
								17	38700	18500	17510	16830	15310	29	23570
								1.4	19230	9200	8690	8360	7610	2.2	11700
								20	42360	20260	19140	18410	16760	32	25770
								2	23690	11330	10710	10300	9370	2.8	14420
								29	52180	24960	23590	22690	20640	41	31760

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards