

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
340/85R 48	W12	353.0	1797.0	841	5521	156D/ 159A8	0.8	1680	2190	1730	1600	1530	1460	1330
							12	3700	4820	3810	3520	3370	3220	2930
	1.6						2520	3290	2600	2400	2300	2190	1990	
	23						5550	7250	5730	5290	5070	4820	4380	
	2.4						3190	4160	3280	3030	2910	2770	2520	
	35						7030	9160	7220	6670	6410	6100	5550	
	3.2						3770	4920	3890	3590	3440	3280	2980	
	46						8300	10840	8570	7910	7580	7220	6560	
	4.5						4600	6000	4740	4380	4200	4000	3640	
	65						10130	13220	10440	9650	9250	8810	8020	